




MECHANICAL DIMENSIONS [TOP VIEW]



SUGGESTED PAD LAYOUT [PCB TOP VIEW]



SCHEMATIC



Electrical Information:

1. TURNS RATIO [9-13] : [2-6]= 0.187 ±2%
2. INDUCTANCE [2-6] = 2.0 mH Nom ±10% @100kHz/1.0V
3. LEAKAGE INDUCTANCE [2-6] : SHORT 9-13 = 4.8 uH Nom @100kHz
4. DCR [2-6] = 450 mohms Nom, DCR [9-13] = 13 mohms Nom,
5. CAPACITANCE 2,6 to 9,13 = 130 pF Nom,@100kHz
6. DIELECTRIC ISOLATION: [2,6]: [9,13], Core > 3000 VAC/60 Sec
DIELECTRIC ISOLATION: [9,13] : CORE > 500 Vdc
7. RoHS Level 6/6 Compliant | Pins 96/4 Sn/Ag Plating
8. Operating Temp Range -55C to +130C [Inclusive of Application Temp Rise]
9. Storage Temp Range -55C to +155C [Materials rated to +170C]
10. Meets IEC-60950-1 Clearance, Creepage, Class II, Pk Working Voltage 1400V
11. Meets IEC 61180-1 Peak Impulse Withstand Voltage 8KV Pk

No.	DESCRIPTION REVISIONS				DATE	APPR
THIRD ANGLE PROJECTION	CHAMPS TECHNOLOGIES					
	SIGN		DATE		Champs-Tech PN P26R6-AC-3206-2M-TP	
	DRAWN		04.25.19		Customer	
	CHKD				Part #:	
	APPR				SIZE A4	SCALE 2:1
TOLERANCES/UNITS IN MM UNLESS OTHERWISE INDICATED XXX ± 0.254 XX ± 0.54 X 0.78 ANGLE ±	ISSUE A	REV 00				